

Tsunami Pump®

your preferred water booster



HOME BOOSTER PUMP series



Low Maintenance



Energy Saving



Over Heating Protection



Anti-Rust Pump Shell



Less Noise Operation



Strong & Durable



Tsunami Pump®

HOME BOOSTER PUMP series

- Multistage stainless steel impeller.
- Advanced welding equipment, heat treatment.
- High strength, no deformation, long life, safe.
- Mechanical seal to ensure watertight in long-time continuous operation.
- Aluminum frame; low-noise and less-vibration and high durability and reliable.
- Continuous duty.

Application

- Pressure boosting for the water on processing line.
- Water treatment
- Air-conditioning system
- Heating and cooling water on industrial processing line
- Water supply and pressure boosting (drinking water, weak chlorine water)
- Fire-fighting system
- Convey thin, clean, non-flammable and non-explosive liquid without solid granules and fibers

Manufacturer Defect Warranty

- Pump : [Residential 2 years] [Commercial 1 year]
- Pressure Tank : 5 years

• Outdoor Service Support Helpline: 017-665 5488

CMH

BASIC HOME WATER PUMP



CMH-K

CMH-IPT

CMF

STAINLESS STEEL WATER PUMP



CMF-K

CMF-IPT

CMS

STAINLESS STEEL INTELLIGENT HOME WATER PUMP















iPC Controller: 3 modes
[PRESSURE] [FLOW] [TIME]



	CMH-K	CMH-IPT	CMF-K	CMF-IPT	CMS
Pump Body	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
Casing	Cast Iron	Cast Iron	Stainless Steel	Stainless Steel	Stainless Steel
Inlet	Cast Iron	Cast Iron	Stainless Steel	Stainless Steel	Stainless Steel
Outlet	Cast iron	Cast iron	Stainless Steel	Stainless Steel	Stainless Steel
Protection Class	IP55	IP55	IP55	IP55	IP55
Dry-Running Protection	✓	✓	✓	✓	✓
Auto Restart					✓
Anti Leaking		✓		✓	✓
Digital Indicator		✓		✓	✓
Adjustable Mode / Setting		✓		✓	✓
Pressure Mode Setting		✓		✓	✓
Count Down Setting					✓
Kick In Pressure Setting		✓		✓	✓
Maintenance Free	✓	✓	✓	✓	✓
Reduce Hammering		✓		✓	
Restart System (Dry Run)		✓		✓	✓
Old House / Pipings (15yrs & above), ABS Piping		✓		✓	✓

PERFORMANCE TABLE

CMH
CMF
CMS

Model	kW / Hp	Pipe Connection		Concurrently in use Normal Shower Head	Max Capacity Flow Rate	
		Inlet	Outlet			
2-30-K 2-30-iPT 2-30-iPC	0.37kW / 0.5Hp	1"	1"	2x  1x 	3.5m ³ /h 3500l/h	
2-40-K 2-40-iPT 2-40-iPC	0.55kW / 0.75Hp			3x  1x 		
2-50-K 2-50-iPT 2-50-iPC	0.55kW / 0.75Hp			4x 		
2-60-K 2-60-iPT	0.75kW / 1.0Hp			4x  1x 		
4-40-K 4-40-iPT 4-40-iPC	0.75kW / 1.0Hp			1 1/4"	4x  2x 	7m ³ /h 7000l/h
4-50-K 4-50-iPT	1.0kW / 1.3Hp				5x  1x 	
4-60-K 4-60-iPT	1.1kW / 1.5Hp	7x 				

PERFORMANCE CURVE

CMH
CMF
CMS

